

Performance Data

Model	Power		Q (m³/h)	1	1.2	1.6	2	2.4	2.8	3.2	Head Range (m)	Packing Dim. (L×W×H) mm	G.W.(kg)	
	kW	HP												
BL(T)2-2	0.37	0.5	H (m)	18	17	16	15	13	12	10	10~18	595x285x360	26.9	31.1
BL(T)2-3	0.37	0.5		27	26	24	22	20	18	15	15~27	595x285x360	27.1	31.4
BL(T)2-4	0.55	0.75		36	35	33	30	26	24	20	20~36	625x285x360	29.1	33.3
BL(T)2-5	0.55	0.75		45	43	40	37	33	30	24	24~45	625x285x360	29.5	33.8
BL(T)2-6	0.75	1		53	52	50	45	40	36	30	30~53	725x285x375	33.3	37.4
BL(T)2-7	0.75	1		63	61	57	52	47	41	35	35~63	725x285x375	33.7	37.8
BL(T)2-9	1.1	1.5		80	78	73	67	61	54	45	45~80	785x285x375	36.6	40.7
BL(T)2-11	1.1	1.5		98	95	89	82	73	64	54	54~98	785x285x375	37.5	41.6
BL(T)2-13	1.5	2		116	114	106	98	89	78	65	65~116	845x285x385	41.4	45.8
BL(T)2-15	1.5	2		134	130	123	112	100	90	73	73~134	885x285x385	42.5	46.9
BL(T)2-18	2.2	3		161	157	148	136	121	108	91	91~161	935x285x385	47	51.3
BL(T)2-22	2.2	3		197	192	180	165	148	130	110	110~197	1045x290x385	49.2	53.5
BL(T)2-26	3	4		232	228	214	198	179	158	130	130~232	1135x290x385	57.9	62

Model	Power		Q (m³/h)	1.5	2	3	4	5	6	Head Range (m)	Packing Dim. (L×W×H) mm	G.W.(kg)	
	kW	HP											
BL(T)4-2	0.37	0.5	H (m)	19	18	17	15	13	10	10~19	595x285x360	27.8	32.9
BL(T)4-3	0.55	0.75		28	27	26	24	20	18	18~28	625x285x360	30.1	35.3
BL(T)4-4	0.75	1		38	36	34	32	27	24	24~38	725x285x375	33.8	39
BL(T)4-5	1.1	1.5		47	45	43	40	34	31	31~47	725x285x375	36	41.2
BL(T)4-6	1.1	1.5		56	54	52	48	41	37	37~56	785x285x375	36.8	42
BL(T)4-7	1.5	2		66	63	61	56	48	43	43~66	845x285x385	40.4	45.9
BL(T)4-8	1.5	2		74	72	70	64	55	50	50~74	845x285x385	41.2	46.7
BL(T)4-10	2.2	3		96	90	87	81	71	62	62~96	885x285x385	45.4	50.9
BL(T)4-12	2.2	3		114	108	104	95	85	75	75~114	935x285x385	46.7	52.2
BL(T)4-14	3	4		136	126	122	112	101	89	89~136	1045x285x385	54.9	60.1
BL(T)4-16	3	4		152	144	140	129	115	101	101~152	1135x290x385	56.6	61.8
BL(T)4-19	4	5.5		183	171	168	153	137	122	122~183	1205x315x390	65.9	71.1
BL(T)4-22	4	5.5		211	200	192	178	160	138	138~211	1285x315x390	68	74.2

Performance Data

Model	Power		Q (m ³ /h)	8	10	12	14	16	18	20	Head Range (m)	Packing Dim. (L×W×H) mm	G.W.(kg)	
	kW	HP												
BL(T)16-2	2.2	3	H (m)	27	26	25	24	22	21	19	19~27	775x325x400	50.7	59.5
BL(T)16-3	3	4		41	40	38	37	34	32	29	29~41	885x325x415	59.6	68.6
BL(T)16-4	4	5.5		54	53	52	49	46	43	38	38~54	945x325x415	68.8	77.8
BL(T)16-5	5.5	7.5		68	67	65	62	58	54	48	48~68	1115x400x490	89.8	98.6
BL(T)16-6	5.5	7.5		82	80	78	74	70	64	58	58~82	1175x400x490	91.7	100.6
BL(T)16-7	7.5	10		96	95	91	87	82	76	68	68~96	1210x400x490	95.9	106.8
BL(T)16-8	7.5	10		110	108	104	99	94	86	77	77~110	1265x400x490	97.3	108.6
BL(T)16-10	11	15		138	136	131	125	118	109	97	97~138	1425x520x560	178	186.8
BL(T)16-12	11	15		166	162	157	150	141	130	116	116~166	1515x520x560	181.8	190.6
BL(T)16-14	15	20		194	190	184	175	166	152	136	136~194	1605x520x560	196.5	204.3
BL(T)16-16	15	20		222	217	210	200	189	174	156	156~222	1695x520x560	200.3	208.2

Model	Power		Q (m ³ /h)	14	16	18	20	22	24	26	Head Range (m)	Packing Dim. (L×W×H) mm	G.W.(kg)	
	kW	HP												
BL(T)20-2	2.2	3	H (m)	27	25	24	23	22	20	18	18~27	775x325x400	58.8	59.6
BL(T)20-3	4	5.5		40	38	37	35	33	30	27	27~40	945x325x415	68.9	75.9
BL(T)20-4	5.5	7.5		54	51	49	47	44	41	37	37~54	1115x400x490	87.7	95.5
BL(T)20-5	5.5	7.5		67	62	60	58	55	50	45	45~67	1115x400x490	91	98.8
BL(T)20-6	7.5	10		81	75	73	70	66	61	55	55~81	1175x400x490	95	104.8
BL(T)20-7	7.5	10		95	89	86	82	77	71	65	65~95	1210x400x490	97.3	107.4
BL(T)20-8	11	15		109	102	99	94	89	82	75	75~109	1335x520x560	174.4	183.3
BL(T)20-10	11	15		136	128	124	118	111	103	95	95~136	1425x520x560	179.4	188.3
BL(T)20-12	15	20		164	154	149	142	133	124	114	114~164	1515x520x560	194.3	202.4
BL(T)20-14	15	20		192	180	174	166	156	145	133	133~192	1605x520x560	198.1	206.4
BL(T)20-17	18.5	25		234	219	212	202	190	177	162	162~234	1805x520x560	220.6	231

Performance Data

Model	Power		Q (m³/h)	30	40	50	60	64	70	Head Range (m)	Packing Dim. (L×W×H) mm	G.W.(kg)	
	kW	HP											
BL(T)64-2-2	7.5	10	H (m)	39	36	33	29	26	23	23~39	1565x565x612	161	171
BL(T)64-2-1	11	15		46	44	40	36	33	30	30~46	1565x565x612	224.8	232.4
BL(T)64-2	11	15		53	51	47	43	40	37	37~53	1565x565x612	224.8	232.4
BL(T)64-3-2	15	20		66	62	56	50	46	41	41~66	1565x565x612	243	251
BL(T)64-3-1	15	20		73	69	63	57	53	48	48~73	1565x565x612	243	251
BL(T)64-3	18.5	25		80	76	71	65	60	56	55~80	1565x565x612	260.3	268
BL(T)64-4-2	18.5	25		92	87	80	71	66	60	60~92	1565x565x612	264	266
BL(T)64-4-1	22	30		100	94	87	78	73	67	67~100	1565x565x612	306.9	314.6
BL(T)64-4	22	30		107	101	94	85	80	74	74~107	1565x565x612	306.9	314.6
BL(T)64-5-2	30	40		121	114	105	95	88	80	80~121	1865x645x662	386.8	394.4
BL(T)64-5-1	30	40		128	121	112	102	95	87	87~128	1865x645x662	386.8	394.4
BL(T)64-5	30	40		136	129	119	109	102	94	94~136	1865x645x662	386.8	394.4
BL(T)64-6-2	30	40		150	142	131	118	110	101	101~150	1865x645x662	393	401
BL(T)64-6-1	37	50		157	149	138	125	117	108	108~157	1865x645x662	415	422
BL(T)64-6	37	50		164	156	145	132	124	115	115~164	1865x645x662	415	422
BL(T)64-7-2	37	50		179	169	156	141	132	121	121~179	2065x695x712	430	438
BL(T)64-7-1	37	50		186	176	163	148	139	128	128~186	2065x695x712	430	438
BL(T)64-7	45	60		193	183	170	155	146	135	135~193	2065x695x712	489.1	496.7
BL(T)64-8-2	45	60		207	196	182	164	154	142	142~207	2065x695x712	493.7	501.4
BL(T)64-8-1	45	60		215	203	189	171	161	149	149~215	2065x695x712	493.7	501.4
BL(T)64-8	45	60		221	210	196	178	168	156	156~221	2065x695x712	493.7	501.4

Model	Power		Q (m³/h)	50	60	70	80	90	100	Head Range (m)	Packing Dim. (L×W×H) mm	G.W.(kg)	
	kW	HP											
BL(T)90-2-2	11	15	H (m)	41	39	36	32	28	22	22~41	1515x515x562	239.8	247.4
BL(T)90-2	15	20		53	50	47	44	40	36	36~53	1515x515x562	239	236
BL(T)90-3-2	18.5	25		68	65	60	55	49	41	41~68	1565x565x612	304.3	312
BL(T)90-3	22	30		81	77	72	67	62	55	55~81	1565x565x612	262	270
BL(T)90-4-2	30	40		98	93	87	80	72	62	62~98	1815x645x662	375.9	383.6
BL(T)90-4	30	40		110	105	100	92	84	76	76~110	1815x645x662	375.9	383.6
BL(T)90-5-2	37	50		126	120	113	104	93	81	81~126	1815x645x662	375.9	383.6
BL(T)90-5	37	50		139	131	124	115	106	94	94~139	1815x645x662	419.8	427.4
BL(T)90-6-2	45	60		155	148	139	129	117	102	102~155	1965x695x712	483	490.7
BL(T)90-6	45	60		168	160	150	141	130	117	117~168	1965x695x712	483	490.7