

馬達,攝氏40度使用環境連續動作型,安全係數1.0

TOTAL ENCLOSED AMBIENT 40 C.CONTINUOUS DUTY, SERVICE FACTOR SS, F:1.0

Output 馬力		Pole 極數	Frame 框號	Full Load Speed RPM	Efficiency 效率	Power Factor 功能因素	Output 電流		Output 扭力值				Rotor GD kg-m ² 轉子 慣重
HP	KW				Full Load (%) 全負載	Full Load (%) 全負載	Full Load (%) 全負載	Start (A)	Full Load Torque kg-m 全負載扭力值	Locked Rotor Torque % 鎖住轉子扭力值	Pull Up Torque % 上拉扭力值	Break Down Torque % 損壞扭力值	
0.5	0.37	4	71	1690	71.0	72.5	2.00	9.0	0.211	320	235	299	0.005
		6	80	1120	70.0	69.0	2.03	10.0	0.324	200	195	210	0.009
		2	80	3400	77.0	91.0	2.62	17.0	0.213	255	220	219	0.005
1	0.75	4	80	1720	81.0	79.2	3.40	20.0	0.422	246	260	219	0.010
		6	90L	1130	78.5	72.5	3.44	20.0	0.642	180	165	220	0.017
		2	90L	3440	82.5	88.0	5.10	35.6	0.434	260	240	309	0.010
2	1.5	4	90L	1720	85.0	84.0	5.50	33.0	0.845	225	160	290	0.017
		6	100L	1145	85.5	72.0	6.36	40.0	1.268	230	205	260	0.059
		2	90L	3440	84.0	89.0	7.60	55.0	0.629	280	250	350	0.013
3	2.2	4	100L	1720	86.5	84.0	8.50	70.0	1.267	270	220	300	0.041
		6	112M	1165	86.5	71.0	9.60	60.0	1.869	180	170	280	0.084
		2	112M	3495	86.5	91.0	12.8	110	1.056	270	250	318	0.038
5	3.7	4	112M	1730	87.5	85.5	13.5	90.0	2.112	209	165	260	0.059
		6	132S	1170	86.5	76.0	14.9	95.0	3.102	190	175	290	0.131
		2	132S	3505	88.5	89.0	18.5	135	1.553	230	190	255	0.063
7.5	5.5	4	132S	1740	88.5	84.0	21.0	150	3.167	275	200	285	0.103
		6	132M	1165	88.5	78.5	21.1	150	4.673	200	175	300	0.189
		2	132S	3510	88.5	85.5	26.0	200	2.112	230	190	309	0.072
10	7.5	4	132M	1750	91.0	87.0	26.0	175	4.172	218	185	274	0.133
		6	160M	1170	88.5	78.0	28.4	220	6.204	280	225	290	0.420
		2	160M	3540	89.5	89.5	36.7	290	3.076	230	190	300	0.147
15	11	4	160M	1760	92.0	87.5	38.0	265	6.186	220	165	250	0.330
		6	160L	1165	89.5	79.0	41.5	285	9.346	260	220	250	0.588
		2	160M	3525	90.2	91.0	47.7	350	4.118	220	160	265	0.183
20	15	4	160L	1750	92.0	88.9	49.0	360	8.276	210	165	245	0.381
		6	180M	1175	90.0	81.0	54.0	365	12.355	245	205	250	0.054
		2	160L	3530	91.0	92.0	58.5	465	5.141	240	175	280	0.237
25	18.5	4	180M	1760	91.7	86.0	62.1	440	10.310	220	205	250	0.657
		6	180L	1175	91.0	82.0	65.6	450	15.444	230	185	250	1.342
		2	180M	3530	91.0	88.0	73.3	520	6.160	220	185	265	0.270
30	22	4	180M	1760	91.7	85.5	74.9	535	12.373	240	195	260	0.715
		6	180L	1175	91.0	81.0	79.7	540	18.533	235	175	250	1.438
		2	180L	3535	91.0	88.0	97.8	700	8.213	235	195	270	0.340
40	30	4	180L	1750	92.5	88.0	96.3	615	16.591	205	170	235	0.810
		6	200L	1180	92.5	85.0	100	670	24.605	225	195	240	2.326
		2	200L	3555	91.7	87.5	122	945	10.209	160	150	300	0.905
50	37	4	200L	1775	92.4	83.0	128	830	20.447	200	180	250	1.481
		6	200L	1180	92.4	86.0	123	845	30.757	220	195	230	2.907
		2	200L	3555	92.4	89.0	143	1085	12.251	150	135	270	1.074
60	45	4	200L	1775	93.0	84.5	149	1050	24.536	200	180	250	1.731
		6	225S	1180	93.0	96.0	147	965	36.908	200	180	230	4.194
		2	225S	3560	93.0	88.0	179	1230	15.292	150	140	300	1.211
75	55	4	225S	1780	93.3	84.0	187	1235	30.584	230	185	220	2.897
		6	225S	1185	93.0	82.0	193	1450	45.940	195	180	290	6.492
		2	250S	3560	93.6	89.5	234	1640	20.389	130	120	280	1.759
100	75	4	250S	1780	94.1	88.5	235	1570	40.779	150	150	250	4.853
		6	250M	1185	93.6	83.5	250	1700	61.254	185	180	260	7.694

備註: 1.所有馬達依照JIS C42 12, IEEE 112測試方法B的標準, CNS 14400
 2.所有上述數字都是實際測試數據。
 3.公差的標準是依 IEC 34-1(確定的最低效率值與此CNS 14400一致)。
 4.圖片尺寸規格若有修改;恕不另行通知